HVRM-T1600M

16 CHANNEL DIGITAL VIDEO RECORDER, H.264

Features

16 CHANNEL DIGITAL VIDEO RECORDER, H.264, LINUX EMBEDDED, 480/120 @ 720X480 (FULL D1), 480/240 @ 720X240 (HALF D1), 480/480 @ 360X240 (CIF), USB BACK UP, UP TO 4TB INTERNAL, BUILT-IN RS232, 485, ALARM/ RELAY, AUDIO, LOOPING, REMOTE CONTROL WITH MOUSE CONTROLLED GUI.

Specification

OPERATION SYSTEM	Embedded LINUXEMBEDDED LINUX
VIDEO INPUT (BNC, 1VP-P)	16
VIDEO OUTPUT	4 BNC (MAIN), 1 VGA
LOOP OUT (BNC, 1VP-P)	16 WITH AUTO-TERMINATION
LIVE DISPLAYS	1, 4, 9, 16
PLAYBACK DISPLAYS	1, 4, 9, 16
VIDEO COMPRESSION	H.264, JPEG
FILE SIZE	2~3KB @ (CIF), 13K @ (FULL D1)
LIVE DISPLAY SPEED	480/400 IPS (NTSC/PAL)
RECORD RESOLUTION	D1, HALF D1, CIF
RECORD SPEED	480/120@720X480 (FULL D1), 480/240@720X240 (HALF D1), 480/480 @360X240 (CIF)
ALARM IN/OUT (RELAY)	16/4
EMERGENCY RECORD MODE	YES
SYSTEM CONTROL	KEY BUTTONS, REMOTE CLIENT, IR REMOTE, USB MOUSE
SYSTEM CONTROL SW	CONTROL CENTRE, WEB BROWSER
PTZ CONTROL	RS485/RS232
VIDEO FORMAT	NTSC/PAL

© 2010 Eyesonic Enterprises Inc. All rights reserved.

AUDIO	4 CHANNEL INPUT, 1 CHANNEL OUTPUT
DISPLAY	BRIGHTNESS, CONTRAST AND COVERT FEATURE
CAMERA TITLE	22 CHARACTERS PER CHANNEL
RECORDING MODE	SCHEDULE, EVEN (PRE/POST), MANUAL (EMERGENCY)
RECORDING QUALITY	5 LEVELS OF COMPRESSION RATE/ RECORD FRAME RATE ADJUSTMENT
PRE/POST RECORDING	PRE: 5 SEC/POST: 60 SEC
MOTION DETECTION	22x15 NTSC/22x18 PAL
SEARCH MODE	DATE/TIME, EVENT ALARM, TEXT, SMART SEARCH (MOTION)
PALYBACK MODES	FORWARD, REVERSE, PAUSE, 1X, 2X, 4X, 8X, 16X, 32X, 64X
MULTIPLEX FUNCTION	SIMULTANEOUS LIVE DISPLAY, PLAYBACK, RECORD, REMOTE MONITORING/PLAYBACK
ALARM NOTIFICATION	AUTOMATIC E-MAIL, INTERNAL BUZZER, RELAY OUT, POP-UP SCREEN, NETWORK EVENT
SUPPORT	INTELLIGENT POWER FAILURE RECOVERY

© 2010 Eyesonic Enterprises Inc. All rights reserved.